

INCH POUND

MIL-PRF-3098/50E

13 April 2010

SUPERSEDING

MIL-PRF-3098/50D

9 December 2004

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR72/U

Reactivated after 9 December 2004 and may be used for new and existing designs and acquisitions.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and [MIL-PRF-3098](#).

Pertinent characteristics: 17Hz to 61 MHz; third mechanical overtone; noncontrolled; series resonance.




FIGURE 1. Crystal unit - CR72/U.

MIL-PRF-3098/50E

Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.183	---	4.65
B	---	.435	---	11.05
C	---	.402	---	10.21
D	---	.530	---	13.46
E	.500	---	12.70	---
F	.016	.019	0.41	0.48
G	---	.150	---	3.81
H	.184	.200	4.67	5.08

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with [MIL-PRF-3098](#).

FIGURE 1. Crystal unit - CR72/U - Continued.

MIL-PRF-3098/50E

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 17Hz to 61 MHz, inclusive.

Capacitance, shunt: 7.0 pF maximum.

Frequency tolerance:

Operating temperature range:  $\pm 50$  ppm.

Equivalent resistance: 40 ohms, maximum.

Mode of oscillation: Third mechanical overtone.

Calibration values:

Resistance: 40 ohm, maximum.

Resistor voltage drop: 0.28 volt.

Rated drive level: 2.0  $\pm 0.4$  mW.

Resonance: Series.

Operating temperature range:  $-55^{\circ}\text{C}$  to  $+105^{\circ}\text{C}$ , inclusive.

Shock (specified pulse):

Frequency change permitted:  $\pm 5$  ppm.

Equivalent resistance change permitted:  $\pm 10$  percent.

Vibration high frequency: [Method 204 of MIL-STD-202](#), test condition A.

Frequency change permitted:  $\pm 5$  ppm.

Equivalent resistance change permitted:  $\pm 10$  percent.

Thermal shock:

Frequency change permitted:  $\pm 5$  ppm.

Equivalent resistance change permitted:  $\pm 10$  percent.

Aging:

Frequency change permitted:  $\pm 5$  ppm.

MIL-PRF-3098/50E

Part or Identifying Number (PIN): CR72/U (followed by specified frequency), see 1.2 of [MIL-PRF-3098](#).

Reference documents. In addition to [MIL-PRF-3098](#), this document references the following:

[MIL-STD-202](#)

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - CR  
Navy - EC  
Air force - 99  
DLA - CC

Preparing activity:

Army - CR

Agent:

DLA - CC

Review activities:

Army - AR, MI  
Navy - AS, CG, MC, OS, SH, TD  
Air Force - 19, 84

(Project 5955-2009-059)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.daps.dla.mil>.